

# BERGEN 190

## SPECIFICATIONS

|                      |   |
|----------------------|---|
| Plank size           | Length: 630-1860 mm<br>Width: 190 mm<br>Thickness: 15(3) mm |
| Box                  | Min 4 planks of 1.86 m<br>2.12 m <sup>2</sup><br>16 kg      |
| Pallet               | 40 boxes  |
| Structure            | 3-layer   |
| Coating              | Matt lacquer  |
| Texture              | Slightly brushed  |
| Standard colour      | Natural, Pure and Mont Blanc                                |
| Grading              | Rustic AB   |
| Top layer type       | Dry sawn veneer   |
| Top layer thickness  | 3 mm  |
| Bevel                | V-groove on the long side                                   |
| Gloss                | 10 ± 5%   |
| Locking system       | Tongue and groove   |
| Type of installation | Advised: glued  |

## STRUCTURE



## INSTALLATION



## PRODUCT CHARACTERISTICS - General

|                       |  |
|-----------------------|--|
| Factor                | Standard - EN 14342                      |
| Density               | 650 kg/m <sup>3</sup> , 15 mm            |
| Reaction to fire      | Dfl-S1                                   |
| Formaldehyde emission | E1                                       |
| PCP                   | ≤ 5 ppm                                  |
| Thermal conductivity  | 0.13 W/mK                                |
| Thermal resistance    | 0.12 m <sup>2</sup> K/W                  |
| Biological durability | Class 1                                  |
| Surface soundness     | ≥ 1.00 N/mm <sup>2</sup>                 |
| Impact resistance     | ECO                                      |
| Moisture level        | 7% - ±2%                                 |
| Floor heating         | Allowed, according to specific standards |