

SPECIFICATIONS

Plank size	Length: 600-1860 mm Width: 190 mm Thickness: 15(3.5) mm
Box	Min 5 planks of 1.86 m 2.12 m ² 16.5 kg
Pallet	40 boxes
Structure	3-layer
Coating	Oxidative dried oil (White, Smoked White, Smoked Natural, Smoked Grey, Smoked Coffee), UV oil (Double Smoked Pure)
Texture	Brushed
Standard colour	White, Smoked White, Smoked Natural, Double Smoked Pure, Smoked Grey, Smoked Coffee
Grading	Rustic B+
Top layer type	Dry sawn veneer
Top layer thickness	3.5 mm
Bevel	V-groove on the long side
Gloss	10 ± 5%
Locking system	Tongue and groove
Type of installation	Advised: glued

STRUCTURE



INSTALLATION



PRODUCT CHARACTERISTICS - General

Factor	Standard - EN 14342
Density	650 kg/m ³ , 15 mm
Reaction to fire	Dfl-S1
Formaldehyde emission	E1
PCP	≤ 5ppm
Thermal conductivity	0.13 W/mK
Thermal resistance	0.12 m ² K/W
Biological durability	Class 1
Surface soundness	NPD
Impact resistance	NPD
Moisture level	7% - ±2%
Floor heating	Allowed, according to specific standards